(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 6 November 2003 (06.11.2003)

PCT

(10) International Publication Number WO 03/091545 A1

(51) International Patent Classification?: F01C 1/344, 21/08

(21) International Application Number: PCT/FI03/00314

(22) International Filing Date: 17 April 2003 (17.04.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 20020793

24 April 2002 (24.04.2002) FI

(71) Applicant and

(72) Inventor: VIITAMÄKI, Tapio [FI/FI]; Lipastinkuja 12, FIN-61330 Koskenkorva (FI).

(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).


(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO utility model (GH), ARIPO patent (GH), ARIPO utility model (GM), ARIPO patent (GM), ARIPO utility model (KE), ARIPO patent (KE), ARIPO utility model (LS), ARIPO patent (LS), ARIPO utility model (MW), ARIPO patent (MW), ARIPO utility model (MZ), ARIPO patent (MZ), ARIPO utility model (SD), ARIPO patent (SD), ARIPO utility model (SL), ARIPO patent (SL), ARIPO utility model (SZ), ARIPO patent (SZ), ARIPO utility model (TZ), ARIPO patent (TZ), ARIPO utility model (UG), ARIPO patent (UG), ARIPO utility model (ZM), ARIPO patent (ZM), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: HYDRAULIC MOTOR



(57) Abstract: The invention relates to a hydraulic motor having an outer casing (1) and eccentric means (11, 12, 8) for rotating a power shaft (5) by means of fluid through a pressure chamber arrangement (14 to 17). The eccentric means comprise an eccentric part (8) formed in the power shaft (5), a first eccentric ring (11) between the outer casing (1) and an inner casing (3), and a second eccentric ring (12) mounted with bearings around the eccentric part and connected fixedly and concentrically to the first eccentric ring, whereby the pressure chamber arrangement is located between the first eccentric ring and the inner casing so that the first eccentric ring drives the power shaft through the second eccentric ring (12), and the eccentric rings (11, 12) form a substantially non-rotating entity that only performs an eccentric movement and by means of this eccentric movement rotates the power shaft.